

CHB45 Closed End Baling Press

dock loading with fully enclosed steel hopper and interface



Specification

Our CHB45 Closed End Baling Press is ideal for those seeking to minimise the space taken up by waste products and make it more manageable.

With fast cycle time, large loading aperture, heavy duty compaction and low noise levels, our CHB45 Closed End Baler is also the perfect choice for those keen to reap the benefits of recycling whether improving your carbon footprint or receiving payment for any recycled materials.

The balers are easy to operate, safe to use and backed by a network of our own engineers to ensure maximum reliability.

IEG products are also covered with a 12 Month Warranty, so you can rely on us to maintain hygienic and sustainable community & commercial spaces.



Technical Information

| COMPACTION FORCE | 54 Tonne |
|------------------|----------|

POWER REQUIREMENT 32A 3Ph + N + E Socket outlet fused at 32Amp D type with local 30 Milliamp RCD protection

If you have an existing supply that doesn't match this specification, please contact **technical@iegemea.com** to check if it's usable or discuss a solution)

MOTOR 11kW 70dB at 3m From Unit **NOISE LEVEL** 50 Seconds CYCLE TIME LOADING APERTURE 1435mm x 1060mm MAXIMUM BALE SIZE 740mm x 1090mm x 1200-1300mm **BALE WEIGHT** 450-500kg (Depending on material)

OVERALL DIMENSIONS 7266mm (L) x 2885mm (H) x 1573mm

Rear Dock Level Bin Lift & Weatherproof Canopy (& Optional Side **VARIANT SHOWN** Platform/Steps)

All machines are built following the CE and UKCA guidance and legislation

The details provided in our specification sheets are for your general information and use only. They are subject to change due to the continual design and build development.









